

PRODUCT SPECIFICATIONS Remote, Local or Automated **Controls** 5 - 80 gpm | 1.2 - 18 m³/h **Variable Flow Water Usage** up to 300 ft | 95 m **Projection Misting Coverage** 260 000 sq. ft 24 200 cubic meters Height 10 to 30 ft | 3 to 10 m Oscillation 330° Voltage 460V | 600V | 380V 50 Hz | 60 Hz Frequency 25 HP | 19 kW Fan **Pump** 25 HP | 19 kW 5 - 80 gpm @ 380 psi 1.2 - 18 m³/h @ 26 Bar **Camlock Water Connection** 1.5 in. or 2 in. (with swivel coupling) V-Flow Central Nozzle Nozzle **Outer Misting Ring** Warranty 1 year V-500 FX

The V-Flow 500 FX is designed for fixed dust emissions locations such as dry bulk storage areas and loading terminals, recycling yards, or aggregate facilities. Available on a 20' tower, the V-Flow 500 FX can achieve more than 250' of distance with all the benefits of our Variable Flow central nozzle and remote control functionality. When multiple units are required for complete coverage, the V-Flow 500 FX's can be completely automated with centralized computer control.



HKD Blue

15 Mercer Road Natick, MA, USA 01760 617-913-7679 gsantry@hkdblue.com



HKD Rlue

5780 Boulevard Sainte-Anne Boischatel, Québec, Canada G0A 1H0 (800) 613-4546 cgrenier@hkdblue.com