

V-400GT

The 40 hp **V-400 GT** comes standard with:

- Remote Control Functionality
- US EPA Tier 4 Final Generator
- **HKD GEYSER** Water Flow Adjustment
- 330 degree programmable oscillation

The next-gen **V-400GT** is designed to match the production of our industry leading **V-500** models while reducing energy and water requirements. This is an ideal unit for projects that require Tier 4 compliant engines.

Applications Include:

- Dust Suppression
- Smoke Emissions Control
- Crushing & Aggregate Handling
- Dry Bulk Transfer & Storage

SPECIFICATIONS

Operation	Remote or Manual
Variable Flow Rates	10 - 50 gpm 1.2 - 18 m ³ /h
Projection	225 ft 69m
Auto. Oscillation	330°
Misting Coverage	146,280 ft ² 13,590m ²
Fan Motor	25 hp 19kw
Fan Capacity	33,000 cfm 56,067m ³ /h
Pump Motor	15 hp 11.2 kw
Pump Capacity	10-60 gpm @ 250-400psi 2-14 m ³ /h @ 17 - 27 bar
Voltage/Frequency	480v @ 60 Hz 600v @ 60 Hz 380v @ 50 Hz



Tier 4 Final Genset

Engine Make	Isuzu
Prime Power	45kW